

ATC1530L 3 Axis Linear Auto Tool Changing CNC Router



Model No.	ATC1530L
Brand Name	WINWIN
FOB Price	US \$ 15,600 – 38,800 / Set
Get Latest Price	lucy@2winmachinery.com
Port	Qingdao
Place of Origin	Shandong Province, China
Payment Terms	T/T, L/C, Western Union, MoneyGram, Escrow
Delivery Details	Within five weeks after receiving the payment
Packaging Details	Standard Plywood Case for Export
Certification	CE, UL, ISO
Warranty	1 Year
After-sales Service Provided	Engineers available to service machinery overseas

Performance Parameter

Number	Description	Parameter
1	X,Y,Z Working Area	1500x3000x300mm
2	Table Size	1530×3540mm
3	X,Y,Z Traveling Positioning Accuracy	±0.03/300mm
4	X,Y,Z Repositioning Accuracy	±0.03mm
5	Table Surface	Vacuum and T-slot Combined (Option: T-slot table)
6	Frame	Welded structure
7	X, Y Structure	Rack and Pinion Drive, Hiwin Rail Linear Bearings
8	Z Structure	Hiwin Rail Linear Bearings and Ball Screw
9	Max. Power Consumption	(Without Spindle) 4.5kw
10	Max. Rapid Travel Rate	45000mm/min
11	Max. Working Speed	30000mm/min
12	Spindle Power	9.0KW
13	Spindle Speed	0-24000RPM
14	Drive Motors	Yaskawa servo
15	Working Voltage	AC 380V/50/60Hz,3PH
16	Command Language	G Code
17	Operating System	Syntec Control System
18	Computer Interface	Enthernet
19	Flash Memory	256M
20	Collet	ER32
21	X,Y Resolution	<0.03mm
22	Software Compatibility	Type3/UcancameV9 software (Option: Artcam software)
23	Running Environment Temperature	0 - 45 Centigrade
24	Relative Humidity	30% - 75%
25	Packing Size	4250x2250x2100mm
26	N.W.	1900KG
27	G.W.	2180KG
28	Optional Parts	3.8KW HSD Auto Spindle
		Dust Collector
		Vacuum Pump
		Rotary System
		Mist-cooling System
		HSD Boring Unit

Materials Cut

Acrylic, ACM, Copper, Brass, Aluminum, PVC, MDF, Melamine plastic, Foam, Melamine, Phenolic, Plywood, HDPE, Solid Surface, Solid Wood, etc.



Samples



Packing & Delivery

