

## ATC2040CB ATC CNC Router with Boring Unit



<b>Model No.</b>	ATC2040CB
<b>Brand Name</b>	WINWIN
<b>FOB Price</b>	US \$ 17,600 – 38,800 / Set
<b>Get Latest Price</b>	<a href="mailto:shining@2winmachinery.com">shining@2winmachinery.com</a>
<b>Port</b>	Qingdao
<b>Place of Origin</b>	Shandong Province, China
<b>Payment Terms</b>	T/T, L/C, Western Union, MoneyGram, Escrow
<b>Delivery Details</b>	Within five weeks after receiving the payment
<b>Packaging Details</b>	Standard Plywood Case for Export
<b>Certification</b>	CE, UL, ISO
<b>Warranty</b>	1 Year
<b>After-sales Service Provided</b>	Engineers available to service machinery overseas

## Performance Parameter

Number	Description	Parameter
1	X,Y,Z Working Area	2000x4000x300mm
2	Table Size	2010x4040mm
3	X,Y,Z Traveling Positioning Accuracy	±0.03/300mm
4	X,Y,Z Repositioning Accuracy	±0.03mm
5	Table Surface	Vacuum and T-slot Combined (Option: T-slot table)
6	Frame	Welded structure
7	X, Y Structure	Rack and Pinion Drive, Hiwin Rail Linear Bearings
8	Z Structure	Hiwin Rail Linear Bearings and Ball Screw
9	Max. Power Consumption	(Without Spindle) 5.5kw
10	Max. Rapid Travel Rate	45000mm/min
11	Max. Working Speed	30000mm/min
12	Spindle Power	9.0KW
13	Spindle Speed	0-24000RPM
14	Drive Motors	Yaskawa servo
15	Working Voltage	AC 380V/50/60Hz,3PH
16	Command Language	G Code
17	Operating System	Syntec Control System
18	Computer Interface	Enthernet
19	Flash Memory	256M
20	Collet	ER32
21	X,Y Resolution	<0.03mm
22	Software Compatibility	Type3/UcancameV9 software (Option: Artcam software)
23	Running Environment Temperature	0 - 45 Centigrade
24	Relative Humidity	30% - 75%
25	Packing Size	5200X2300X1700mm
26	N.W.	2450KG
27	G.W.	2670KG
28	Optional Parts	3.8KW HSD Auto Spindle
		Dust Collector
		Vacuum Pump
		Rotary System
		Mist-cooling System
		HSD Boring Unit

## Materials Cut

Acrylic, ACM, Copper, Brass, Aluminum, PVC, MDF, Melamine plastic, Foam, Melamine, Phenolic, Plywood, HDPE, Solid Surface, Solid Wood, etc.



## Samples



## Packing & Delivery

